

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Super Bright Max GENERAL USE: Cleaning agent PRODUCT DESCRIPTION: Colorless liquid, acrid acid odor	SUPERIOR SOLUTIONS
--	-----------------------

MANUFACTURER'S NAME Superior Solutions	DATE PREPARED: October 29, 2008 SUPERSEDES: New	Page 1 of 4
ADDRESS (NUMBER, STREET, P.O. BOX) 3991 Hwy. 171	TELEPHONE NUMBER FOR INFORMATION (337) 794-1829	
MATERIAL SAFETY DATA SHEET DeRidder, LA 70634	COUNTRY USA	EMERGENCY TELEPHONE NUMBER (337) 794-1829

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW Toxic, harmful and corrosive to the skin, eyes, nose, mucous membranes, respiratory tract and gastrointestinal tract, or any tissue with which it comes in contact. Hazard Symbol- C,T. Risk phrases R 23/24/25, 34
POTENTIAL HEALTH EFFECTS

INHALATION: Inhaling HF vapors can seriously damage the lungs. Delayed reactions up to and including fatal pulmonary edema may not be apparent for hours after the initial exposure. Airborne concentrations of 10-15 ppm will irritate the eyes, skin, and respiratory tract; 30 ppm is considered "Immediately Dangerous to Life and Health" (IDLH) and may have irreversible health effects; above 50 ppm, even brief exposure may be fatal.
SKIN: Corrosive and extremely irritating; may produce severe chemical burns which are slow in healing. Subcutaneous tissue may be affected, becoming blanched and bloodless. In 20% - 50% HF concentrations, burns can be delayed 1 to 8 hours. Concentrations of less than 20% HF may cause delayed painful erythema up to 24 hours after contact. Latent skin burns and necrosis with slow healing can occur even at concentrations of 2% HF. Delayed burns begin with itching sensation and proceed to burning and pain.
EYES: Corrosive; Causes immediately severe burns of the eye and eyelids. If not quickly removed by thorough irrigation with water, there may be prolonged or permanent visual impairment or total loss of sight.
INGESTION: Corrosive. Swallowing hydrofluoric acid causes severe burns of the mucous membrane of the mouth, throat, esophagus and the stomach.
CARCINOGENICITY NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS	CAS #	EINECS #	% (by weight)	OSHA PEL		ACGIH TWA		RQ LBS
				PPM	MG/M3	PPM	MG/M3	
Hydrofluoric acid (a,b,c,d,e,f)	7664-39-3	231-634-8	7 - 13	3		3 C		100
Sulfuric Acid (a,c,d)	7664-93-9	231-639-5	10 - 30		1		1	1000
Phosphoric acid (c)	7664-38-2	231-633-2	3 - 7		1		1	5000
Ethylene glycol monobutyl ether (a,g)	111-76-2	203-905-0	3 - 7	50	240		20	

(a,c) See Section 15
(b) Indicates that the Resource Conservation and Recovery Act (RCRA) has determined the waste for this chemical is listed as hazardous and must be handled according to regulations in 40 CFR 260-281.
(d) Indicates an Extremely Hazardous Substance, if your facility has a designated amount of this substance, Threshold Planning Quantity (TPQ) in inventory, the regulations of 40 CFR 355 and 370 apply, including submission of Tier I / Tier II forms every March 1.
(e) A "C" in the OSHA PEL or ACGIH TWA column indicates ceiling limits, the concentration that should not be exceeded during any part of the working exposure.
(f) OSHA regulation (29 CFR 1910.119), monitor and control safety at certain types of industrial facilities. Compliance is triggered by specified quantities of specific chemicals. Minimum threshold quantity for this Highly Hazardous Chemical is 1000 lbs.
(g) Indicates an employee's skin exposure shall be prevented or reduced to the extent necessary in the circumstances through the use of gloves, coveralls, goggles, or other appropriate equipment.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Super Bright Max
October 29, 2008

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; get immediate medical attention with emphasis on hydrofluoric acid exposure. If breathing is difficult, supply oxygen. If breathing has stopped, begin artificial respiration.

SKIN: Remove contaminated clothing while flushing affected area with drenching shower for 5 minutes. Launder contaminated clothing before reuse; seek immediate medical attention with emphasis on hydrofluoric acid exposure. Apply 2½% Calcium Gluconate ointment to contacted area.

EYES: Remove contact lenses. Immediately flush eyes for 5 minutes in clear running water while holding eyelids open; seek immediate medical attention with emphasis on hydrofluoric acid exposure. Irrigate open eyelids with 500 to 1,000 cc's of 1% Calcium Gluconate in saline solution.

INGESTION: Drink high amounts of calcium based antacid in water followed by milk or milk of magnesia; DO NOT induce vomiting; never give anything by mouth to an unconscious person; seek immediate medical attention with emphasis on hydrofluoric acid exposure.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED) Non-flammable	FLAMMABLE LIMITS AUTOIGNITION TEMPERATURE: Not determined	LEL: Not applicable	UEL: Not applicable	NFPA CLASS: None
--	--	---------------------	---------------------	-------------------------

GENERAL HAZARDS: Product is corrosive. Products of combustion include compounds of carbon, hydrogen, oxygen, and fluorine, including carbon monoxide.

EXTINGUISHING MEDIA
Carbon dioxide, water fog, dry chemical, chemical foam. Do not use solid stream of water.

FIRE FIGHTING PROCEDURES
Firefighters should be equipped with NIOSH approved fully enclosed self-contained breathing apparatus with plastic window in the hood. Keep containers cool with water spray to prevent container rupture due to steam buildup; CAUTION - material is corrosive.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Contact with B:C extinguisher powder may produce large amounts of carbon dioxide. Material can generate explosive hydrogen gas on contact with certain metals.

HAZARDOUS COMBUSTION PRODUCTS
Smoke, fumes, oxides of carbon, fluorine vapors

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Caution - Corrosive. Allow only Trained Hazardous Response Personnel in the area. Confine and absorb into approved absorbent; place material into approved containers for disposal; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions; refer to SARA Title III, Section 313, 40 CFR 372 for reporting requirements. Do not discharge into lakes, ponds, streams or public waters.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: This product will attack glass, concrete and certain metals. Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - material is corrosive. Keep this and other chemicals out of reach of children. Refer to 40 CFR 355 & 370 for regulations pertaining to items classified as Threshold Planning Quantities as shown in Section 3, Hazardous Ingredients.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS
The use of local exhaust ventilation is recommended. Use corrosion-resistant ventilation equipment.

PERSONAL PROTECTION:
RESPIRATORY PROTECTION: None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. A chemical cartridge respirator with acid cartridge is recommended. If concentration exceeds capacity of cartridge respirator, a self - contained breathing apparatus is advised. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

PROTECTIVE GLOVES: Required. Saranex, Barricade, Chemrel, Responder, and Butyl rubber are recommended. Do not use Nitrile Rubber, Polyvinyl Alcohol or Polyvinyl Chloride.

EYE PROTECTION: Chemical safety goggles with side shields. Refer to 29 CFR 1910.133 or European Standard EN166.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Chemical resistant butyl rubber apron, or other approved chemical resistant equipment should be worn to prevent skin contact. Do not use Nitrile Rubber, Polyvinyl Alcohol or Polyvinyl Chloride.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Safety showers and safety eyewash nearby.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Super Bright Max
October 29, 2008

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE 17 mm Hg @ 20° C	VAPOR DENSITY (AIR = 1) > 1
SPECIFIC GRAVITY (WATER = 1) 1.230	EVAPORATION RATE (CCL4 = 1) < 1
SOLUBILITY IN WATER Complete	FREEZING POINT 32° F (0° C)
pH < 1.0	APPEARANCE AND ODOR Colorless liquid, acrid acid odor
BOILING POINT 212° F (100° C)	PHYSICAL STATE Liquid
VISCOSITY Like that of water	VOLATILE ORGANIC COMPOUNDS (Total VOC's) 2.43 pounds / gallon

SECTION 10 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: X	CONDITIONS TO AVOID: Extreme temperatures.
-------------------------------------	--

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong alkalies, most metals, cyanides, sulfides, glass and ceramics.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes or vapors, fluorine and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X	CONDITIONS TO AVOID: None. Non-hazardous endothermic polymerization may occur in both the liquid and gas phases.
---	--

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Ingredients	CAS #	EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Hydrofluoric acid (a,b,c,d,e,f)	7664-39-3	231-634-8	Not established	1276 / ppm / 1H Inhalation - rat
Sulfuric Acid (a,c,d)	7664-93-9	231-639-5	2140 mg / kg Oral - rat	510 mg / m3 / 2H Inhalation - rat
Phosphoric acid (c)	7664-38-2	231-633-2	1530 mg / kg Oral - rat	> 850 mg / m3 Inhalation - rat
Ethylene glycol monobutyl ether (a,g)	111-76-2	203-905-0	470 mg / kg Oral - rat	450 ppm / 4H Inhalation - rat

SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Do not flush to sanitary sewer or waterway. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for corrosive materials containing Hydrofluoric Acid. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Hydrofluoric acid & sulfuric acid mixture

DOT HAZARD CLASS / Pack Group: 8 (6.1) / I	IATA HAZARD CLASS / Pack Group: 8 (6.1) / I
REFERENCE: 49 CFR 173.201, .243	IMDG HAZARD CLASS: 8 (6.1) / I
UN / NA IDENTIFICATION NUMBER: UN 1786	RID/ADR Dangerous Goods Code: 8 (6.1) / I
LABEL: CORROSIVE, POISON	UN TDG Class / Pack Group: 8 (6.1) / I
HAZARD SYMBOLS: C T	Hazard Identification Number (HIN): 886

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Super Bright Max
October 29, 2008

SECTION 15 - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories
Immediate health

313 Reportable Ingredients:

(a) Indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CERCLA (Comprehensive Response Compensation and Liability Act)

(c) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture = 1,000 lbs) or greater amounts, according to 40 CFR 302.

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: D1B, E

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

WGK Water Quality Index: 1

VbK Index: Not applicable

EC Risk Phrases

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R34 Causes burns.

SYMBOL(S) REQUIRED FOR LABEL



EC Safety Phrases

S7/9 Keep container tightly closed and in a well ventilated place.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible.)

SECTION 16 - OTHER INFORMATION

Specific toxicity tests have not been conducted on this product. Our hazard evaluation is based on Information from similar products, the ingredients, technical literature, and/or professional experience.

HMIS HAZARD RATINGS

HEALTH	3	* = Chronic Health Hazard	2 = MODERATE
FLAMMABILITY	0	0 = INSIGNIFICANT	3 = HIGH
PHYSICAL HAZARD	1	1 = SLIGHT	4 = EXTREME

PERSONAL PROTECTIVE EQUIPMENT C Safety Glasses, Gloves, Apron

REVISION SUMMARY:

This MSDS has been revised in the following sections:
No changes noted

MSDS Prepared by:

Comprehensive Data Base, Inc.
P.O. Box 686
Seffner, FL 33583 USA
(863) 644 - 3298 www.compdatabase.com or www.msds.cc

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.